



DIMENSIONAL DATA							
DIM.	INCHES			MILLIMETERS			
	MIN.	MAX.	REF.	MIN.	MAX.	REF.	
A	4.094	4.156		103.99	105.56		
B	.781	.844		19.83	21.44		
E	2.937	3.063		74.60	77.80		
F	1.850	2.190		46.99	55.63		
G	9.000	10.300		228.60	261.62		
H	.375	.563		9.53	14.30		
I	.700	1.000		17.78	25.40		
J	.115	.200		2.92	5.08		
K	.450	.520		11.43	13.21		
L			1.225			31.12	
M	3.200	3.625		81.28	92.08		
N	2.980	3.010		75.95	76.45		
P	1.490	1.510		37.85	38.35		
Q	1.950	2.100		49.53	53.34		
S	.437			11.10			
T	3.165	3.425		80.39	87.00		

NOTES:

1. REF. DIMENSIONS ARE FOR INFORMATION ONLY AND ARE NOT REQUIRED FOR INSPECTION PURPOSES.
2. .040 MAX. RUNOUT OF GRID CONTACT SURFACE WITH RESPECT TO THE AXIS DETERMINED BY ANODE AND OUTER FILAMENT CONTACT SURFACE.
3. STAMP BOTH SIDE 180° APART.

9-TH5-6

LTR	DESCRIPTION OF CHANGE	SCO	DATE	BY	Part No.	Code
E	REDRAWN ON CAD	25452	10/04/99	SM/DB	TH5-6	
F	DEL. TUBE TYPE NO. TH5-6	26559	05/23/02	SM/KA		
DRAWN: S. SINGH 10/04/99 ENGR APPR:					SCALE: NONE	NO.
CHK'D: D. BANKS 10/05/99 SUPERSEDES:					FILE PATH: L:\OUTLINE\TH5-6	TH5-6
ELECTRON DEVICE						F